



GM Data Interface with SWC 2000-2013

Visit [AxxessInterfaces.com](https://www.axxessinterfaces.com) for more detailed information about the product and up-to-date vehicle specific applications.

INTERFACE COMPONENTS

- AXDIS-CL2 interface
- AXDIS-CL2 harness
- 16-pin harness with stripped leads
- 4-pin to 4-pin resistor pad
- Female 3.5mm connector with stripped leads

INTERFACE FEATURES

- Designed for non-amplified, or analog/digital amplified models
- Provides accessory power (12-volt 10-amp)
- Retains R.A.P. (Retained Accessory Power)
- Provides NAV outputs (parking brake, reverse, speed sense)
- Retains chimes
- Retains audio controls on the steering wheel
- Retains OnStar®/OE Bluetooth®
- Adjustable OnStar® level
- Retains the factory AUX-IN jack
- Retains RSE (Rear Seat Entertainment) *
- Retains SAT (Satellite radio)
- Retains balance and fade (excludes digital amplified models)
- Micro "B" USB updatable

* The RSE must be activated by the factory radio

APPLICATIONS

Visit this link or scan QR code for Vehicle Applications
<https://www.axxessinterfaces.com/product/AXDIS-CL2>

Product Info



SALES 386-257-2956

REV. 9/30/24

What Fits My Vehicle? See the Vehicle Fit Guide at [AxxessInterfaces.com](https://www.axxessinterfaces.com)