



# AXLOC-BM1 INTERFACE KIT



## INTERFACE FEATURES

- Designed to provide (2) channels of low-level audio output from the factory system.
- Allows for the installation of an amplifier for speakers or subwoofers.
- Gain Controller included to adjust the overall output.
- 12v-500mA remote wire activated with signal sense.
- 55-watts per channel.
- Designed for non-amplified vehicles.

**Note:** A single pole double throw (SPDT) relay is recommended when installing multiple amplifiers.

## BMW/MINI/VW LOC (Line Output Converter) AXLOC-BM1 (for Non-Amplified Vehicles) 2001-2017

Visit [AxxessInterfaces.com](http://AxxessInterfaces.com) for more detailed information about the product and up-to-date vehicle specific applications.

## INTERFACE COMPONENTS

- AXLOC-BM1 Wiring Harness
- Gain Controller
- 12v-500mA Remote Wire
- Auxiliary Cable

## APPLICATIONS

BMW		Mini		Volkswagon			
3-Series	2002-2006	Clubman	2008-2014	Beetle	2012-2015	Jetta	
5-Series	2001-2003	Convertible	2009-2015	CC	2009-2017	Sportswagon	2010-2014
M3	2002-2006	Coupe	2012-2015	EOS	2007-2016	Passat	2002-2015
X3	2004-2010	Hatchback	2007-2013	Golf	2002-2014	R32	2007-2008
X5	2001-2006	Roadster	2012-2015	GTI	2006-2014	Tiguan	2009-2015
Z4	2003-2008			Jetta	2002-2015	Toureg	2004-2010

For dash disassembly instructions, refer to [metraonline.com](http://metraonline.com). Enter the year, make, and model of the vehicle in the **Vehicle Fit Guide** for **Radio Install Kits**.

SALES 386-257-2956

REV. 12/15/22

What Fits My Vehicle? See the Vehicle Fit Guide at [AxxessInterfaces.com](http://AxxessInterfaces.com)

© COPYRIGHT 2022 METRA ELECTRONICS CORPORATION