



GM LAN-11 OnStar interface 2006-2012

INTERFACE FEATURES

- Provides accessory power (12-volt 10-amp)
- Maintains the retained accessory power (R.A.P.) feature
- Can be used in non-amplified, or amplified models
- Retains warning chimes
- Provides NAV outputs (parking brake, reverse, speed sense)

- Pre-wired AXSWC harness (AXSWC sold separately)
- Retains OnStar/OE Bluetooth
- Adjustable volume for chimes and OnStar
- Retains balance and fade
- Micro "B" USB updatable

APPLICATIONS

CHEVROLET		PONTIAC		PONTIAC (CONT)		SATURN	
Cobalt	2007-2010	G5	2007-2009	Solstice	2006-2009	Aura	2007-2009
HHR	2006-2011	G6	2010			Sky	2006-2009
Malibu	2008-2012	G6*	2009				

* 5th digit of VIN must be a J, K, or L

TABLE OF CONTENTS

Connections to be made	2-3
Installing the AXGMLN-34.....	4
Programming the AXGMLN-34.....	4
Adjusting the AXGMLN-34	4
Troubleshooting.....	5

INTERFACE COMPONENTS

- AXGMLN-34 interface
- AXGMLN-34 harness
- 16-pin harness with stripped leads
- 4-pin to 4-pin resistor pad harness

TOOLS REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink
- Tape • Wire cutter • Zip ties

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.

CONNECTIONS TO BE MADE

From the 16-pin harness with stripped leads to the aftermarket radio:

- Connect the **Red** wire to the accessory wire.
Note: If installing an AXSWC (sold separately), connect the (2) **Red** wires on the AXGMLN-34 harness as well.
- Connect the **Orange/White** wire to the illumination wire. (If the aftermarket radio has no illumination wire, tape off the **Orange/White** wire).
- Connect the **Blue/White** wire to the amp turn on wire (this wire must be connected to hear sound from the factory amplifier).
- Connect the **Brown** wire to the mute wire of the aftermarket radio. If the radio has no mute wire, tape it off and disregard it.
- Connect the **White** wire to the left front positive speaker output.
- Connect the **White/Black** wire to the left front negative speaker output.
- Connect the **Gray** wire to the right front positive speaker output.
- Connect the **Gray/Black** wire to the right front negative speaker output.
- Tape off and disregard the following (4) wires, they will not be used in this application:
Green, Green/Black, Purple, Purple/Black.

The following 3 wires are for an aftermarket multimedia/navigation radio that provide these wires (if not required, tape them off and disregard them):

- Connect the **Light Green** wire to the parking brake wire (if applicable).
- Connect the **Blue/Pink** wire to the speed sense wire (V.S.S.) (if applicable).
- Connect the **Green/Purple** wire to the reverse wire (if applicable).

From the AXGMLN-34 harness to the aftermarket radio:

- Connect the **Black** wire to the ground wire.
- Connect the **Yellow** wire to the battery wire.
- If installing an AXSWC (sold separately), connect the (2) **Red** wires to accessory power.
- The **Black/Yellow** wire is used for OnStar level adjustment for models that do not come equipped with steering wheel controls. See OnStar Level Adjustment for further instructions.
- Connect the **Red** and **White** RCA jacks to the audio AUX-IN jacks from the aftermarket radio.

Continued on the next page

CONNECTIONS TO BE MADE *(CONT.)*

For amplified models only:

- Connect the **Green** wire to the left rear positive speaker output.
- Connect the **Green/Black** wire to the left rear negative speaker output.
- Connect the **Purple** wire to the right rear positive speaker output.
- Connect the **Purple/Black** wire to the right rear negative output.
- Disconnect the 4-pin harness located between the 16-way and 22-way connector, and then connect the supplied 4-pin to 4-pin resistor pad harness.

For non-amplified models only:

- Cut the resistors off from the **Green**, **Green/Black**, **Purple**, and **Purple/Black** wires below the heat shrink.
- Connect the **Green** wire to the left rear positive speaker output.
- Connect the **Green/Black** wire to the left rear negative speaker output.
- Connect the **Purple** wire to the right rear positive speaker output.
- Connect the **Purple/Black** wire to the right rear negative output.

Note: The 4-pin to 4-pin resistor pad harness will not be used in this application.

Note: The relay attached to the AXGMLN-34 harness is only for audible turn signal clicks. No extra steps are required to retain this feature, so leave the relay as-is.

12-pin pre-wired AXSWC harness:

This harness is to be used in conjunction with the optional AXSWC (not included) to retain steering wheel controls. If the AXSWC is not being used, disregard this harness. If it will be used, please refer to the AXSWC instructions for radio connections and programming. Disregard the harness that comes with the AXSWC.

DIN jack:

Disregard the DIN jack.

INSTALLING THE AXGMLN-34

With the key in the off position:

- Connect the 16-pin harness with stripped leads, and the AXGMLN-34 harness, into the interface.
- If an AXSWC (sold separately) will be used, do not connect it until the AXGMLN-34 is programmed and fully functional.

Attention! Do not connect the AXGMLN-34 harness to the wiring harness in the vehicle just yet.

PROGRAMMING THE AXGMLN-34

For the steps below, the L.E.D. located inside the interface can only be seen while active. The interface does not need to be opened to see the L.E.D.

1. Start the vehicle.
2. Connect the AXGMLN-34 harness to the wiring harness in the vehicle. The L.E.D. will initially be **Green** to indicate the interface is powered.
3. After a few seconds the L.E.D. will turn on solid **Red** while the interface automatically programs to the vehicle. The radio will shut off at this point. This process should take 5 to 30 seconds.
4. After the interface is programmed, the L.E.D. will turn on solid **Green**, and the radio will come back on, indicating programming was successful.
5. Test all functions of the installation for proper operation, before reassembling the dash.
6. If the interface fails to function, refer to “Troubleshooting”.

ADJUSTING THE AXGMLN-34

Chime level adjustment:

- With the vehicle on, turn it off and leave the keys in ignition. Open the driver's door; chimes will be heard.
- Wait 10 seconds, and then with a small screwdriver, turn the potentiometer clockwise to raise the chime level; counterclockwise to lower the chime level.
- When the chime level is at a desired level, remove the keys from the ignition. This will lock the chime volume at its current level.

OnStar level adjustment:

- Press the OnStar button to activate it.
- While OnStar is speaking, press the VOLUME UP or VOLUME DOWN buttons on the steering wheel to raise or lower the OnStar level.
- If the vehicle does not come equipped with steering wheel controls, find the Black/Yellow wire on the AXGMLN-34 harness.
- While OnStar is speaking, tap the **Black/Yellow** wire to ground. Once the OnStar level is set, it will stay at that level until the **Black/Yellow** wire is tapped to ground again.

Resetting the Axxess interface

1. The **Blue** reset button is located inside the Axxess interface, between the two connectors. The button is accessible outside the Axxess interface, no need to open the Axxess interface.
2. Press and hold the reset button for two seconds, then let go to reset the Axxess interface.
3. Refer to “Programming the Axxess Interface” from this point.







AXGMLN-34

INSTALLATION INSTRUCTIONS



IMPORTANT

If you are having difficulties with the installation of this product, please call our Tech Support line at 1-800-253-TECH. Before doing so, look over the instructions a second time, and make sure the installation was performed exactly as the instructions are stated. Please have the vehicle apart and ready to perform troubleshooting steps before calling.



KNOWLEDGE IS POWER

Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry. Log onto www.installerinstitute.com or call 800-354-6782 for more information and take steps toward a better tomorrow.



Metra recommends MECP certified technicians