



HE-RLC-4B/HE-RLC-4W

INSTALLATION INSTRUCTIONS

COMPATIBILITY: HE-RGB-R1, HE-RGB-K4, HE-RGB-K8, HE-RGBW-R1, HE-RGBW-K4, HE-RGBW-K8, HE-CHASE-R1, HE-CHASE-K4, HE-CHASE-K8, HE-RGB-EX4, HE-RGBW-EX4, HE-CHASE-EX4

ROCK LIGHT COVER INSTALLATION:

1. Follow the steps for installation of the lights. Use the template for drilling the necessary holes using a 5/32" drill bit.

NOTE: If you want to tap the hole to use the included hardware without the nut, use a 3.3mm tap bit.


2. Place the light cover over the light and install the light on the mounting surface. (Figures A & B)
3. Place the screw through the light cover, the light and through the mounting surface and tighten the 7mm nut. (Figure C)



(Figure A)



(Figure C)



(Figure B)

REQUIRED TOOLS

- Phillips Bit Driver
- 3.3mm Tap Bit (Optional)
- 7mm Wrench
- Power Drill
- 5/32" Drill Bit

WHAT'S IN THE BOX

- (4) Rock Light Covers
- (8) Stainless steel machine screws
- M4 (0.7) x 28mm
- (8) 7mm Stainless steel nuts with nylon inserts

