



DL-DL1



DL-DL4S



DL-DL4R

DL-DL1/DL-DL4S/DL-DL4R DRIVING LIGHTS


SALES 386-257-2956

PRODUCT OVERVIEW

Traditionally styled driving lights mount with lower bracket located in the center. With a crisp pattern, these light are a great compliment to any primary lighting system. The DL-DL4S and DL-DL4R are the same light in a different form factor. Both are considered 4" lights. These are a staple light in the off-roading scene to light up trails. With a medium 60 degree flood, they light up the area while still putting ample light down the trail.

Common Specs

- Housing Material: die-cast aluminum
- Color: black
- Lens Material: polycarbonate
- Hardware: stainless steel
- Electronics: integrated-epoxy encapsulated
- Operating Temperature: -40° F to 140° F
- Protection: reverse polarity

DL-DL1

- Wattage: 40W *
- Raw Lumens: 2880lm*
- Current Consumption @13.8V: 2.9A*
- IP Rating: IP67
- Input Voltage: 10-30V DC
- Color Temperature: 6500K
- Beam Pattern: spot 10°
- Cube Dimensions: 1.9"H x 6.3"W x 2.5"D

*Total value for set of two lights

DL-DL4R/DL-DL4S

- Wattage: 54W*
- Raw Lumens: 3510lm*
- Current Consumption @13.8V: 3.4A*
- IP Rating: IP67
- Input Voltage: 10-30V DC
- Color Temperature: 6500K
- Beam Pattern: flood 60°
- Cube Dimensions: 5.0"H x 4.3"W x 2.2"D

*Total value for set of two lights


WARNING:

 Cancer and Reproductive Harm
www.P65Warnings.ca.gov