



5.6” Replacement LED Headlight with Partial Halo for Motorcycles

HE-BHL561 (Black Front Face)

HE-SHL561 (Silver Front Face)

**Applications: Motorcycles with a 5.6”
round headlight**

Tools Needed – Phillips Screwdriver

Instructions:

Refer to the motorcycle’s instructional manual for proper headlight removal.

For most applications follow these steps:

1. Remove trim ring (if applicable) by removing (1) Phillips screw at bottom of trim ring.
2. Unplug the motorcycle’s harness from the headlight and remove headlight.
3. Plug the H4 harness into the new **HEISE** LED headlight.

4. **Halos** - Take the **RED** wire located at the base of the headlight plug and wire it to a 12v accessory that will turn on with the key in the ignition or it can be directly wired to a switch that you can turn on and off.
5. Replace trim ring (if applicable).
6. Turn on headlight to ensure connections were properly made.
7. Adjust headlight pattern if needed.

Specifications:

(8) 5 watt CREE LEDs

White partial angel eye halo connects to ignition

1350LM low beam, draws 1.6a @ 13.8v

1770LM high beam, draws 2.1a @ 13.8v

DOT approved for on-road use

LED color temp: 6500K

Polycarbonate lens

H4 connector

Designed for use with most motorcycles using a 5.6" headlight



1-800-221-0932

www.HeiseLED.com

460 Walker Street, Holly Hill, FL 32117