



7" LED Headlight Adapter Bracket for Jeep JL with Retaining Ring HE-JLB7 (Adapter)

Applications: 2018 and newer Jeep JL with the 9" round headlight

Tools Needed – Pry tool or flat head screwdriver, Phillips Screwdriver, 10mm socket with extension and ratchet

Instructions:

Refer to the manufactures' instructional manual for proper headlight removal.

- Open hood and remove the 6 push pin clips across the top of the grille and remove them with a flat head screwdriver or pry tool.
- Pressure clips will be the only things holding the grille to the Jeep at this point. Pull from the bottom corner of the grille to release the clips and remove grille.
- Remove the (3) 10mm bolts from the headlight bucket; these are used to hold each headlight into the vehicle.
- Unplug and remove the headlight.
- Remove the three Phillips head screws from the adapter bracket and remove the retaining ring from the bracket.
- Place the included 7" rubber gasket into the retaining ring and fold rubber gasket tabs around the ring's mounted points.
- Place adapter bracket in where the removed headlight bucket was and replace the three previously removed 10mm bolts.
- Plug the **included** H4 to OE adapter into the factory headlight harness.

NOTE: Due to electrical inconsistencies found in some Jeeps a decoder may be needed. If so then plug the H4 decoder (included with HEISE 7" round headlights) into the H4 to OE adapter.

- Plug the new 7" round headlight into the H4 to OE adapter before placing headlight into the bracket.
- Place headlight into bracket making sure to align location tabs with the ones found on the bracket.
- Use three Phillips screws to secure the headlight, retaining ring, and rubber gasket to the bracket.
- Repeat previous steps to install the other headlight.
- Turn on headlights to ensure everything is in working order and to make sure they are aimed properly.
- Adjustments to the headlight aim can be made by adjusting the spring loaded screws found on the adapter bracket.
- Reinstall grille by lining up pressure clip and pushing the grille back into place.
- Reattach the 6 push pin clips across the top of the grille to complete install.

1-800-221-0932 www.HeiseLED.com
460 Walker Street, Holly Hill, FL 32117