



## **7" Replacement Headlights for JEEP WRANGLERS**

**HE-PBHL701 (Black Front Face)**

**HE-PSHL701 (Silver Front Face)**

### **Applications: 1997-Current Jeep Wranglers**

**Tools Needed** – Flat head screwdriver, T-15 Torx bit

#### **Instructions:**

1. Open hood and remove the 6 push pin clips across the top of the grille and remove them with a flat head screwdriver.
2. Unsnap grille, unplug turn signals that are located in the grille, and remove grille.
3. Remove the (4) T-15 Torx screws from the ring that is holding each headlight in the vehicle.
4. Unplug and remove the headlight.
5. For **1997-2006** Jeep Wranglers continue to **step 7**.

For **2007 to current** Jeep Wranglers, the included H4 adapter and Canbus decoder are needed to complete install.

6. Plug in the new **HEISE** headlight, and secure it in place with the previously removed ring and T-15 Torx screws.
7. Repeat previous steps to install the other headlight.
8. Turn on headlights and make sure they are aimed properly so not to blind oncoming traffic.
9. Reinstall grille by plugging turn signals back in and snap grille back into place.
10. Reattach the 6 push pin clips across the top of the grille to complete install.

### **Specifications:**

(2) 10 watt and (4) 5 watt Cree LEDs per housing

2000LM low beam draws 1.8a @ 13.8v

3000LM high beam draws 2.6a @ 13.8v

DOT approved for on-road use

LED color temp: 6500K

H4 connector

H4 to H13 and CANBUS adapters included for 2007 and newer  
Jeep Wranglers

Dust/Water resistance: IP67



**1-800-221-0932**

**[www.HeiseLED.com](http://www.HeiseLED.com)**

**460 Walker Street, Holly Hill, FL 32117**